





# Laboratory Electrical Fixtures


## Electrical Receptacles and Switches

All flush mount fixtures furnished complete with device, stainless steel face plate and electrical box. Pedestals are furnished with device, wrinkled black epoxy powder coated pedestal box, stainless steel face plate, tank nipple and locknut. All devices and boxes are UL listed.




Type 2 and Type 3 pedestal boxes furnished with 3/4" IPS tank nipple, Type 7 and Type 8 pedestal boxes furnished with 1" IPS tank nipple.		Flush mount single gang box	Single Wide Pedestal Type 2 – Single Faced Type 3 – Double Faced			Flush mount double gang box	Double Wide Pedestal Type 7 – Single Faced Type 8 – Double Faced	
Electrical Device	Color	Type 1	Type 2	Type 3	Type 6	Type 7	Type 8	
120 Volt AC, 20 amp, specification grade, 3-wire polarized grounding duplex receptacle.	 Black Ivory	<b>0581-1K</b> <b>0581-1V</b>	<b>W-0581-2K</b> <b>W-0581-2V</b>	<b>W-0581-3K</b> <b>W-0581-3V</b>	<b>0581-6K</b> <b>0581-6V</b>	<b>W-0581-7K</b> <b>W-0581-7V</b>	<b>W-0581-8K</b> <b>W-0581-8V</b>	
<b>Isolated ground</b> 120 Volt AC, 15 amp, duplex receptacle.	 Orange	<b>0581-1G</b>	<b>W-0581-2G</b>	<b>W-0581-3G</b>	<b>0581-6G</b>	<b>W-0581-7G</b>	<b>W-0581-8G</b>	
240 Volt AC, 20 amp, specification grade, 3-wire polarized grounding receptacle.	 Black Ivory	<b>0582-1K</b> <b>0582-1V</b>	<b>W-0582-2K</b> <b>W-0582-2V</b>	<b>W-0582-3K</b> <b>W-0582-3V</b>	<b>0582-6K</b> <b>0582-6V</b>	<b>W-0582-7K</b> <b>W-0582-7V</b>	<b>W-0582-8K</b> <b>W-0582-8V</b>	
<b>Ground Fault Protected,</b> 120 Volt AC, 20 amp, specification grade, duplex receptacle.	 Black Ivory	<b>0656-1K</b> <b>0656-1V</b>	<b>W-0656-2K</b> <b>W-0656-2V</b>	<b>W-0656-3K</b> <b>W-0656-3V</b>				
<b>Ground Fault Protected,</b> 120 Volt AC, 20 amp, duplex receptacle and 3-wire polar-ized grounding receptacle.	 Black Ivory				<b>0657-6K</b> <b>0657-6V</b>	<b>W-0657-7K</b> <b>W-0657-7V</b>	<b>W-0657-8K</b> <b>W-0657-8V</b>	
Single pole, 120/240 Volt AC, 20 amp toggle switch.	 Black Ivory	<b>0655-1K</b> <b>0655-1V</b>	<b>W-0655-2K</b> <b>W-0655-2V</b>	<b>W-0655-3K</b> <b>W-0655-3V</b>				

## Electrical Plugmolding



**0578-03 3' Plugmold** Provided with six 3-wire outlets on 6" centers. Has an insulated grounding connector. Receptacles are 15 amp., 125 volt AC only and are prewired together into a single circuit. Metal raceway is finished in a buff color.



**0578-05 5' Plugmold** Provided with five 3-wire outlets on 12" centers. Has an insulated grounding connector. Receptacles are 15 amp., 125 volt AC only and are prewired together into a single circuit. Metal raceway is finished in a buff color.