

MATERIAL SAFETY DATA SHEET

MANUFACTURED BY: Kewaunee Scientific Corporation
2700 West Front Street
PO box 1842
Statesville, North Carolina 28627-1842

Date of Preparation: July 21, 2003 Telephone: 704-873-7202
Telephone: 704-871-3238

SECTION I—PRODUCT IDENTIFICATION

Product Name: Polish for Kemresin Tops
Product Number: 129-66
Product Class: Wax based polish

SECTION II—HAZARDOUS INGREDIENTS

Ingredient [CAS No.]	%	TLV	FP.	LEL	VP
Aliphatic Hydrocarbons	60	200ppm	100 F	0.9%	29
Turpentine [8006-64-2]	5	100ppm	91 F	0.8%	4
Paraffin Wax [8002-74-2]	5	2mg/m3	390 F	NA	NA

SECTION III—PHYSICAL DATA

Evaporation Rate: Slower than air
Vapor Density: Heavier than air
Boiling Range (F): 310 – 399 (F.)
% Volatile Volume: 64%

SECTION IV—FIRE AND EXPLOSION DATA

Flammability Classification: Flammable

Flash Point: See section II

LEL: See section II

Extinguishing Media: Carbon dioxide, Dry chemical, Foam

Unusual Fire and Explosion and Explosion Hazards: Keep containers tightly closed. Isolate from heat, sparks, or open flames. Closed containers may explode when exposed to extreme heat. During emergency conditions, exposure to decomposition products may cause a health risk. Symptoms may not be immediately apparent. Obtain medical attention.

Special Fire Fighting Procedures: Full protective equipment including self-contained-breathing-apparatus should be used, fog nozzles are preferable. Water may be used to cool closed containers exposed to extreme heat.

SECTION V—HEALTH HAZARD DATA

Threshold Limit Value: See section II

Effects of Overexposure: Overexposure to vapor may cause headaches, dizziness, or unconsciousness. Prolonged liquid contact will dry and de-fat skin leading to irritation and possible dermatitis.

Emergency and First Aid Procedures: If overcome by vapor, remove from area to fresh air. Call physician. If breathing has stopped start mouth to mouth resuscitation. For contact with eyes, flush with water for 15 minutes. For skin contact, wash with water.

SECTION VI—REACTIVITY DATA

STABLE: YES

INCOMPATIBILITY: AVOID STRONG OXIDIZERS

Hazardous decomposition products: Fire will cause carbon dioxide, carbon monoxide and oxides of nitrogen.

Hazardous Polymerization: WILL NOT OCCUR

SECTION VII—SPILL OR LEAK PROCEDURES

Steps to be taken if material spills or leaks: Remove sources of ignition. Ventilate and absorb with inert material.

Waste disposal method: Incinerate in approved facility. Do not incinerate closed container. Dispose of in accordance with Federal, State and Local regulations.

SECTION VIII—PERSONAL PROTECTION

Respiratory Protection: Normally not needed. If in a confined space, a supplied air mask should be used.

Ventilation: Mechanical (general) exhaust is acceptable.

Protective Gloves: Required for prolonged contact.

Eye Protection: Wear safety glasses or goggles

Other PPE: None

SECTION IX—OTHER PRECAUTIONS

Precautions to be taken in handling and storing: Contents are flammable. Keep away from heat, sparks or open flames. Use only with adequate ventilation. Avoid contact with skin and eyes. Wash hands after use. Keep containers closed when not in use.

Product Name: Polish for Kemresin Tops

page 4

SECTION X—ADDITIONAL INFORMATION

SARA 311/312 Categories for this product

ACUTE: YES

CHRONIC: YES

FIRE: YES

PRESSURE: NO

REACTIVITY: NO